



FLEXIBLE ROLLER CHIAN COUPLING



Chain couplings are designed as robust, Compact, coupling consisting of two steel Chain pinions for keying to the shafts, encircled By a balanced, quickly detachable special Duty roller chain.

Couplings are available with our without aluminums cover. Aluminums Encloser casing ensures complete protection and lubrication. Chain coupling accomodate;s limited alignment errors, perfect alignment.

Lubrication

Couplings operating without covers under fairly clean conditions will give satisfactory service provided they are periodically (weekly) brushed thoroughly with ball bearing grease of medium consistency.

Couplings operating with covers should be kept filled with a good quality ball bearing grease of soft or medium consistency.

DIMENSIONS				ALLUMINIUM COVER				
Coupling Size	Min Bore	Max Bore	C	D	T	W	A	B
SR 3012	10	16	27	45	65	4	69	59
SR 4012	10	22	35	60	79	7	75	68
SR 4014	10	28	43	69	9	7	85	75
SR 4016	12	32	50	77	79	7	90	70
SR 5014	15.88	35	53	86	96	7.9	102	85
SR 5016	15.88	42	61	96	96	7.9	110	86
SR 5018	15.88	48	71	106	98	7.9	121	86
SR 6018	19.05	60	88	126	121	8.9	149	90
SR 6020	19.05	68	100	138	121	9.00	161	100
SR 6022	19.05	76	110	150	121	9.00	173	110
SR 8018	25	80	115	170	150	16	195	130
SR 8022	25	95	140	201	150	16	220	132
SR 10020	40	110	160	231	200	18	258	178
SR 12018	50	119	169	254	260	24	292	220

11, VASTA HOUSE, GR. FLOOR, JANMABOOMI MARG,
FORT, MUMBAI - 400001, INDIA.

TEL: 91-22-22844307/22871995/22872449

FAX: 91-22-22873597/22870770

E-mail: info@wiperdrive.com, WEB SITE: www.wiperdrive.com