





NG/NGF TYPE CLUTCHES



NGF



NG

-OIL /GREASED FILLED,READY TO FIT.

-TRANSMIT TORQUE (POWER) in one directions, opposite free.

-Contains individually spring loaded rollers ,ball bearing support.

Function:-Feeding.

-Indexing

-Back stopping

-Overrunning

CODENO.	DH7		F	D	W	L	D1	D2	E Nm	S	TORQUE
	OVER	UPTO									
NG 17/ NGF	12	18	25	73	30	40	49	60	4	M6	90
NG 25/ NGF	20	25	37	87	30	40	61	75	4	M6	185
NG 35/ NGF	25	35	49	107	30	45	73	88	4	M8	315
NG 40/ NGF	35	45	61	117	30	45	85	102	4	M8	460

All dimensions are in m.m

Other sizes on request.

Dimensions/Design subject to modifications.

Shaft must be hardened & ground if selected NFG

Shaft dia is to be controlled within h6/ j6.

11,VASTA HOUSE,GR.FLOOR,JANMABOOMI MARG,
FORT ,MUMBAI-400001 ,INDIA.

TEL:91-22-22844307/22871995/22872449

FAX:91-22-22873597/22870770

E-mail:info@wiperdrive.com,WEB SITE:www.wiperdrive.com