



RIGID COUPLING



TYPE	SIZE	KW AT 100 RPM	PR MAX. BORE	PRT		OUTSIDE DIA	OVERALL LENGTH		LENGTH THRU'BORE	
				BUSH SIZE	BORE RANGE		PR	PRT	PR	PRT
PR	020	1.06	28	-	--	89	66	-	30	-
PR/ PRT	030	2.30	38	1008	10-25	127	82	46	38	20
	038	4.80	42	1108	10-28	132	96	46	45	20
	042	6.40	48	1215	12-32	146	112	82	53	38
	048	9.63	55	1615	14-42	171	122	82	58	38
	058	16.90	65	2017	14-50	193	136	94	65	44
PR	070	29.9	75	2525	16-60	216	152	136	73	65
	075	36.5	80	-	-	254	176	-	85	-
PR/ PRT	085	53.4	90	3030	24-75	279	200	160	97	76
	105	100.0	120	3535	35-90	330	234	186	114	90
	120	149.0	130	4040	40-100	370	264	212	129	102
	135	213.0	150	4545	55-110	419	294	238	144	114
	150	292.0	170	5050	70-127	457	330	264	160	127
PR	170	470.0	190	-	-	533	376	-	183	-
	190	575.0	215	-	-	597	422	-	206	-
	215	750.0	240	-	-	660	474	-	232	-

11,VASTA HOUSE,GR.FLOOR,JANMABOOMI MARG,

FORT ,MUMBAI-400001 ,INDIA.

TEL:91-22-22844307/22871995/22872449

FAX:91-22-22873597/22870770

E-mail:info@wiperdrive.com,WEB SITE:www.wiperdrive.com