




STANDARD RESILIENT COUPLING



COUPLING NO.	RATINGHP/100 R.P.M	O.D. (mm)	HUB. LENGTH L (mm)	REMSPACER A(mm)	GAPB (mm)	PILOT BORE (mm)	(mm)	SAFE SPEED	R.APPROX .WEIGHTT(Kg)
10	0.60	106	38	53	0.8	10	28	5600	3
20	0.95	121	38	53	0.8	12.5	38	4675	5
30	1.55	144	44	59	0.8	16	40	4400	6
40	2.55	170	51	59	0.8	16	54	3300	9
60	4.05	191	51	81	0.8	16	54	3150	12
70	6.05	197	56.5	81	0.8	16	62	2875	16
80	9.05	221	64	81	0.8	25	77	2400	21
90	12.05	256	70	81	0.8	25	90	2075	28
100	18.05	276	89	81	0.8	25	107	1800	42
105	35.1	296	101.5	130	1.6	38	107	1725	55
110	45.1	323	102	149	1.6	50	122	1525	62
115	65.1	335	102	149	1.6	50	121	1475	70
120	90.1	374	114	149	1.6	50	145	1300	105
125	125.1	426	126	149	1.6	50	165	1100	150
130	175.1	431	141	179	3.21	74	157	1100	173
135	240.1	431	141	179	3.21	74	157	1100	179
140	275.1	491	152	179	3.21	90	172	1000	205
145	350.1	491	152	179	3.21	90	172	1000	218

11, VASTA HOUSE, GR. FLOOR, JANMABOOMI MARG,
FORT, MUMBAI - 400001, INDIA.

TEL: 91-22-22844307/22871995/22872449

FAX: 91-22-22873597/22870770

E-mail: info@wiperdrive.com, WEB SITE: www.wiperdrive.com