



Gravity Rack



HXZG is FIFO type rack which uses gravity and incline to transport goods. You can store and take out goods at the same time.

Gravity Rack is composed of vertical rack and roller rail. FIFO (First in and First out]. Slideway and rack is assembled and disassembled easily, drive placidly and safely. Store large goods and pallet. Slideway gradient is about 4%. Surface Treatment is epoxy powder sprayed.

Loading capacity:

F~Light duty	100K	F<300KG
L~Medium duty	300KG	F<800KG
M~Heavy duty	800KG	F<1 000KG
H~Super heavy	1 000KG	F<1 200KG

Caption List

Type	HXZG: Gravity Rack	XZG: Gravity Slideway
Pallet Width	800. 1 000. 11 00. 1200	
Rack Height	1100. 1300. 1400. 1500	
Depth	nD+300 (Slideway Length)	
Slideway Height	150	
Slideway Width	W+50 [Out Width-W+130)	
Loading Capacity	<300	300<Loading<800 800<Loading<1200
Roller	1.300. JOA ACA (Ø1 2)P=75.100.125.150.175	
Frame	Angle iron L40X75X3	V-iron (40X80X3) V-iron (40X80X3)
Damper	G1	GE .G3 G4

Damper

Type	Loading (KG)	Specification	Exterior Color
G1	100-300	F-Light duty	Short roller (D), Long roller (C)
G2	300-500	L-Medium duty	Short roller (D), Long roller (C)
G3	500-1000.	M-Heavy duty	Short roller (D), Long roller (C)
G4	800-1200	H-Super heavy	Lang roller (C)

11, VASTA HOUSE, GR. FLOOR, JANMABOOMI MARG,
FORT, MUMBAI - 400001, INDIA.

TEL: 91-22-22844307/22871995/22872449

FAX: 91-22-22873597/22870770

E-mail: info@wiperdrive.com, WEB SITE: www.wiperdrive.com