



**EP20S/EP44S  
EP25G/EP55G  
EP15L/EP33L  
EP20L/EP44L  
EP20ES/EP44ES  
EP25HB/EP55HB**

- Safe and easy operation, no oil leakage
- 3-position control: up, neutral, down
- Equipped with overload valve
  - Special size requirements available

Model	EP20S	EP25G	EP15L	EP20L	EP20ES	EP25HB
Specification	Stainless	Galvanized	Low profile	Low profile	With scale	With brake
Capacity (standard fork size)	2000kg	2500kg	1500kg	2000kg	2000kg	2500kg
Overall fork width	540mm,685mm					
Standard Fork Length	1150,1220mm					
Lowered Height	85mm	85/74mm	51m	51mm	85mm	85mm
Lifting Height	200mm					
Load Wheel	Single,Tandem Nylon,PU,steel					
Steering Wheel	NY	NY	NY/PU	NY/PU	NY/PU/RB	NY/PU/RB
Self Weight	80kg					

**11,VASTA HOUSE,GR.FLOOR,JANMABOOMI MARG,  
FORT ,MUMBAI -400001 ,INDIA.**

**TEL:91-22-22844307/22871995/22872449**

**FAX:91-22-22873597/22870770**

**E-mail:[info@wiperdrive.com](mailto:info@wiperdrive.com),WEB SI TE:[www.wiperdrive.com](http://www.wiperdrive.com)**