



## HORIZONTAL TAPER GRID RESILIENT COUPLING



SIZE	COUPLING RATING nM	MAX rpm	MIN BORE mm	MAX BORE mm	CPLG. W. KG.	MR <sup>2</sup> KGM <sup>2</sup>	DIMENSIONS IN MM					
							A	B	C	D	I	GAP
2020	41	4500	13	27	1.0	0.0014	102	94	47.5	39.7	67	3.2
2030	135	4500	13	35	2.4	0.0012	111	98	47.5	49.2	68	3.2
2040	225	4500	13	44	3.2	0.0013	118	103	50.8	57.2	70	3.2
2050	393	4500	13	51	5.2	0.007	138	124	60.3	66.7	79	3.2
2060	621	4350	19	57	7.1	0.012	151	130	63.5	76.2	92	3.2
2070	904	4125	19	68	10.1	0.018	162	156	76.2	87.3	95	3.2
2080	1864	3800	25	83	17.7	0.045	194	181	88.9	104.8	116	3.2
2090	3350	3600	25	95	24.5	0.0787	213	200	98.4	123.8	122	3.2
2100	5300	2440	42	108	41.3	0.18	251	245	120.6	142.1	156	4.8
2110	8478	2250	42	117	53.6	0.27	270	250	127	160.4	163	4.8
2120	12478	2025	60	137	28.7	0.51	308	305	149.2	179.4	192	6.4
2130	18078	1900	66	165	118	0.98	347	335	161.9	212.5	195	6.4
2140	25937	1850	66	184	176	1.85	384	375	164.1	254	201	6.4
2150	37000	1500	108	215	228	3.45	453	372	183	270	272	6.4
2160	51000	1350	120	240	310	5.82	502	402	193	305	278	6.4
2170	67805	1225	135	265	448	10.42	567	431	216	356	307	6.4
2180	94000	1100	150	300	315	18.1	630	484	239	394	321	6.4
2190	124000	1050	150	335	776	26.14	675	524	260	437	325	6.4
2200	169000	900	178	360	1057	43.49	757	565	280	498	356	6.4

- COUPLING WEIGHT AND MR WITH NO BORE
- MAX BORE STATED ABOVE USE RECTANGULAR PARALLEL KEYWAYS TO QS 4235 PT 1972 OR DW 6885 SHT 1 1969.

OTHER COUPLING AVAILABLE ARE SPACER AND HALF SPACER MODELS. ALSO COUPLING WITH DISC OR DRUM BRAKES CAN BE SUPPLIED.

11, VASTA HOUSE, GR. FLOOR, JANMABOOMI MARG,  
FORT, MUMBAI - 400001, INDIA.

TEL: 91-22-22844307/22871995/22872449

FAX: 91-22-22873597/22870770

E-mail: [info@wiperdrive.com](mailto:info@wiperdrive.com), WEB SITE: [www.wiperdrive.com](http://www.wiperdrive.com)