



S.I NO.	OUTPUT SPEED IN rpm FROM to	DRIVE SIZE				MODEL
		S1		S2		
		POWER KW-P	T-MAX NM	POWER KW-P	T-MAX NM	
01	14-70	1.1-2	165	2.2-2	330	R48
02	10-50	1.1-2	225	2.2-2	550	R64
03	7-35	1.1-2	320	2.2-2	640	R96
04	6.5-32.5	0.75-4	230	1.5-4	460	R48
05	5.5-27.5	1.1-2	400	2.2-2	800	R118
06	5-25	0.75-4	295	1.5-4	590	R64
07	4-20	0.55-6	190	1.1-6	380	R48
08	3.5-17.5	0.75-4	420	1.5-4	840	R96
09	3-15	0.55-6	255	1.1-6	510	R64
10	2.5-12.5	0.75-4	585	1.5-4	1170	R118
11	2-10	0.55-6	368	1.1-6	736	R96
12	1.5-7.5	0.55-6	405	1.1-6	810	R118

SL.NO.	OUT SPEED R.P. M.		DRIVE SIZE				MODEL
	FROM	TO	S1		S2		
			P KW -P	T -MAX NM	PKW-P	T-MAX NM	
1.	640	3200	1.1-2	5	2.2-2	10	B
2.	320	1600	0.75-4	5	1.5-4	10	B
3.	320	1600	1.1-2	8	2.2-2	16	R2
4.	200	1000	0.55-6	5	1.1-6	10	B
5.	200	1000	1.1-2	14	2.2-2	28	R3
6.	160	800	0.37-8	5	0.75-8	10	B
7.	160	800	0.75-4	8	1.5-4	16	R2
8.	160	800	1.1-2	19	2.2-2	38	R4
9.	106	530	0.75-4	14	4.5-4	28	R3
10.	106	530	1.1-2	28	2.2-2	56	R6
11.	80	400	0.75-4	19	1.5-4	38	R4
12.	80	400	1.1-2	33	2.2-2	66	R8
13.	67	335	0.55-6	14	1.1-6	28	R3
14.	54	270	0.75-4	29	1.5-4	58	R6
15.	54	270	1.1-2	55	2.2-2	110	R12
16.	50	250	0.55-6	29	1.1-6	58	R4
17.	43	215	0.75-4	35	1.5-4	70	R7.4
18.	40	200	0.75-4	33	1.5-4	66	R8
19.	40	200	1.1-2	73	2.2-2	146	R16
20.	33	165	0.55-6	28	1.1-6	57	R6
21.	27	135	0.75-4	55	1.5-4	110	R12
22.	27	135	1.1-2	110	2.2-2	220	R24
23.	25	125	0.56-6	32	1.1-6	64	R8
24.	20	100	0.75-4	73	1.5-4	146	R16
25.	17	85	0.55-6	55	1.1-6	110	R12
26.	14	70	0.75-4	110	1.5-4	220	R24
27.	13	65	0.55-6	73	1.1-6	146	R16
28.	10.6	53	0.75-4	130	1.5-4	260	R30
29.	8	40	0.55-6	110	1.1-6	220	R24
30.	7	35	0.37-8	105	0.75-8	210	R24
31.	7	35	0.55-6	208	1.1-6	416	R30

P-POWER RATING IN Kw BY NUMBER OF POLES INM=0.1 kg. m.

T-TORQUE WHICH CAN BE TRANSMITTED AT OUT PUT SHAFT IN NM

SPEED OF MOTOR AT A FREQUENCY OF 50 CYCLES

POLE SPEED 2=2800 RPM 4-1400 RPM

6=900 RPM 8-700 RPM

MOUNTING-B3-FOOT MOUNTED(HORIZONTAL)

B14-FLANGE MOUNTED(VERTICAL)

BY MOUNTING DOUBLE SPEED MOTOR SPEED

RANGE CAN BE EXTENDED UP TO 10:1 RATIO

11,VASTA HOUSE,GR.FLOOR,JANMABOOMI MARG,
FORT ,MUMBAI-400001 ,INDIA.

TEL:91-22-22844307/22871995/22872449

FAX:91-22-22873597/22870770

E-mail:info@wiperdrive.com, WEB SITE:www.wiperdrive.com