



EPT-20-20A
EPT-20-45A

- Ergonomic operating handle and controls
- Special option for entry and exist rollers
- Double pallet long forks option
- Comfortable rider platform
- Big size is available
- Two lift cylinders and one extra central cylinder, ensure stable operation
- Strong and reliable forks
 - Single or double load wheel option



Model			EPT-20-13	
Characteristics	1	Capacity	kg	540 685
	2	Load Center	mm	1300
	3	Power Device		600
	4	Operator type		Battery
	5	Wheel(Drive/Load)		Rider
	6	Wheel quantity		Polyurothane/Polyurothane
Specification			km/h	1D+4L/1D+2L
	7	Maximum speed	m/s	6 8
	8	Maximum lifting speed	m/s	0.056 0.06
	9	Maximum Lowering speed	%	0.057 0.059
Dimensions	10	Gradeability	mm	5 7
	11	Lifting Height	mm	120
	12	Ground clearance+fork thivkness	mm	85
	13	Raised height	mm	205
	14	Height rider platform	mm	240
	15	Height from ground to instrument face		870
	16	Fork thivkness	mm	55
	17	Overall length	mm	2077 2127
	18	Fork lenght	mm	1150 1200
	19	Body length	mm	927
	20	Overall width	mm	802
	21	Overall fork width	mm	540 685
	Driving system	22	Size of load wheel	mm
23		Size of steering wheel	mm	Ø48*65
24		Min.outside turning radius	mm	1872 1922
25		Fork width	mm	185
26		Aisle width(800* 1200mm pallet):horixonal/ vertical Aata/Ast3	mm	1630 2245
27		Aisle width(1000* 1200mm pallet):horixonal/ vertical Aata/Ast3	mm	1833 2245
Driving system	28	Bsttery type		Traction
	29	Voltage/Capacity	v/Ah	24/210
	30	Driving Motor	kw	2.2
	31	Lifting Motor	kw	2
	32	Control System		Curtis Mos
	33	Traveling brake		Regenerateel
	34	Parking brake		Electric

11, VASTA HOUSE, GR. FLOOR, JANMABOOMI MARG,
FORT, MUMBAI-400001, INDIA.

TEL: 91-22-22844307/22871995/22872449

FAX: 91-22-22873597/22870770

E-mail: info@wiperdrive.com, WEB SITE: www.wiperdrive.com