



Manual Stacker



- Effortless lifting at an economical price
- This lift is designed to handle skids, pallets, tools and dies, position work, feed machinery, and other handling tasks
- Units is operated by hydraulic foot pump together with handle, making lifting effortless, also foot pedal or handle lowering valve
- Hydraulic cylinder with chrome-plated ram, also master fitted with heavy-duty roller bearings, with flow control valve located at base of lift cylinder that regulates lowering speed for safety
- Steer with rasr swivel casters for ease maneuverability, safety screen, foot operated swovel caster parking brake
- Quick lifting for your choice
- Wheel brake is satandar
- Roller chain with over 5 times capacity yield

Model			MSE500		MSE1000 MSA1000		MSE1500 MSA1500		
Lifting height		mm	1600	2500	1600	2500	1600	2500	
Capacity		kg	500		1000		1500		
Load center		mm	600		600		600		
Overall height	A	Lowered height of fork	mm	2010	1770	2010	1770	2010	1770
		Raised height	mm	2010	2970	2010	2970	2010	2970
Times of lifting to top		Standard		98-105	150-160	98-105	150-160	98-105	150-160
		Double pump		60-65	100-110	60-65	100-110	60-65	100-110
		Quick lift pump		55-60		55-60			
Overall fork width/lenght(MSE500/1000/1500)		mm	560*1150		560*1150		560*1150		
Overall legs width/lenght(MSA1000/1500)		mm			1067		1067		
Fork width		mm	160		160		160		
Self width		kg	160	280	210	310	246	330	
Dimensions of wheel	Steel wheel	mm	Ø150		Ø150		Ø150		
	Front wheel	mm	Ø80		Ø80		Ø80		

11, VASTA HOUSE, GR. FLOOR, JANMABOOMI MARG,
FORT, MUMBAI - 400001, INDIA.

TEL: 91-22-22844307/22871995/22872449

FAX: 91-22-22873597/22870770

E-mail: info@wiperdrive.com, WEB SITE: www.wiperdrive.com